

NAME

gsasl_client_start - API function

SYNOPSIS

```
#include <gsasl.h>
```

```
int gsasl_client_start(Gsasl * ctx, const char * mech, Gsasl_session ** sctx);
```

ARGUMENTS

Gsasl * ctx libgsasl handle.

const char * mech
 name of SASL mechanism.

Gsasl_session ** sctx
 pointer to client handle.

DESCRIPTION

This functions initiates a client SASL authentication. This function must be called before any other `gsasl_client_*`() function is called.

Return value: Returns **GSASL_OK** if successful, or error code.

REPORTING BUGS

Report bugs to <bug-gsasl@gnu.org>.

General guidelines for reporting bugs: <http://www.gnu.org/gethelp/>

GNU SASL home page: <http://www.gnu.org/software/gsasl/>

COPYRIGHT

Copyright (C) 2002-2022 Simon Josefsson.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gsasl** is maintained as a Texinfo manual. If the **info** and **gsasl** programs are properly installed at your site, the command

```
info gsasl
```

should give you access to the complete manual. As an alternative you may obtain the manual from:

<http://www.gnu.org/software/gsasl/manual/>