

NAME

gsasl_mechanism_name - API function

SYNOPSIS

```
#include <gsasl.h>
```

```
const char * gsasl_mechanism_name(Gsasl_session * sctx);
```

ARGUMENTS

Gsasl_session * sctx

libgsasl session handle.

DESCRIPTION

This function returns the name of the SASL mechanism used in the session. The pointer must not be deallocated by the caller.

Return value: Returns a zero terminated character array with the name of the SASL mechanism, or NULL if not known.

SINCE

0.2.28

REPORTING BUGS

Report bugs to <bug-gsasl@gnu.org>.

General guidelines for reporting bugs: <http://www.gnu.org/gethelp/>

GNU SASL home page: <http://www.gnu.org/software/gsasl/>

COPYRIGHT

Copyright (C) 2002-2022 Simon Josefsson.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **gsasl** is maintained as a Texinfo manual. If the **info** and **gsasl** programs are properly installed at your site, the command

```
info gsasl
```

should give you access to the complete manual. As an alternative you may obtain the manual from:

gsasl_mechanism_name(3)

gsasl

gsasl_mechanism_name(3)

<http://www.gnu.org/software/gsasl/manual/>