

**NAME**

gsasl\_property\_set - API function

**SYNOPSIS**

```
#include <gsasl.h>
```

```
int gsasl_property_set(Gsasl_session * sctx, Gsasl_property prop, const char * data);
```

**ARGUMENTS**

Gsasl\_session \* sctx

session handle.

Gsasl\_property prop

enumerated value of Gsasl\_property type, indicating the type of data in *data* .

const char \* data

zero terminated character string to store.

**DESCRIPTION**

Make a copy of *data* and store it in the session handle for the indicated property *prop* .

You can immediately deallocate *data* after calling this function, without affecting the data stored in the session handle.

Return value: **GSASL\_OK** iff successful, otherwise **GSASL\_MALLOC\_ERROR**.

**SINCE**

0.2.0

**REPORTING BUGS**

Report bugs to <bug-gsasl@gnu.org>.

General guidelines for reporting bugs: <http://www.gnu.org/gethelp/>

GNU SASL home page: <http://www.gnu.org/software/gsas/>

**COPYRIGHT**

Copyright (C) 2002-2022 Simon Josefsson.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

**SEE ALSO**

The full documentation for **gsasl** is maintained as a Texinfo manual. If the **info** and **gsasl** programs are properly installed at your site, the command

**info gsasl**

should give you access to the complete manual. As an alternative you may obtain the manual from:

**<http://www.gnu.org/software/gsasl/manual/>**