

NAME

gssd - Generic Security Services Daemon

SYNOPSIS

gssd [-d] [-h] [-v] [-s *dir-list*] [-c *file-substring*] [-r *preferred-realm*]

DESCRIPTION

The **gssd** program provides support for the kernel GSS-API implementation.

The options are as follows:

- d** Run in debug mode. In this mode, **gssd** will not fork when it starts.
- h** Enable support for host-based initiator credentials. This permits a kerberized NFS mount to use a service principal in the default Kerberos 5 keytab file for access. Such access is enabled via the `gssname` option for the `mount_nfs(8)` command.
- v** Run in verbose mode. In this mode, **gssd** will log activity messages to syslog using LOG_INFO | LOG_DAEMON or to stderr, if the **-d** option has also been specified. The minor status is logged as a decimal number, since it is actually a Kerberos return status, which is signed.
- s *dir-list***
Look for an appropriate credential cache file in this list of directories. The list should be full pathnames from root, separated by ':' characters. Usually this list will simply be `/tmp`. Without this option, **gssd** assumes that the credential cache file is called `/tmp/krb5cc_<uid>`, where `<uid>` is the effective uid for the RPC caller.
- c *file-substring***
Set a file-substring for the credential cache file names. Only files with this substring embedded in their names will be selected as candidates when **-s** has been specified. If not specified, it defaults to `"krb5cc_"`.
- r *preferred-realm***
Use Kerberos credentials for this realm when searching for credentials in directories specified with **-s**. If not specified, the default Kerberos realm will be used.

FILES

/etc/krb5.keytab Contains Kerberos service principals which may be used as credentials by kernel GSS-API services.

EXIT STATUS

The **gssd** utility exits 0 on success, and >0 if an error occurs.

SEE ALSO

gssapi(3), syslog(3), mount_nfs(8)

HISTORY

The **gssd** manual page first appeared in FreeBSD 8.0.

AUTHORS

This manual page was written by Doug Rabson <*dfr@FreeBSD.org*>.