

**NAME**

**krb5\_get\_forwarded\_creds**, **krb5\_fwd\_tgt\_creds** - get forwarded credentials from the KDC

**LIBRARY**

Kerberos 5 Library (libkrb5, -lkrb5)

**SYNOPSIS**

```
#include <krb5.h>
```

*krb5\_error\_code*

```
krb5_get_forwarded_creds(krb5_context context, krb5_auth_context auth_context, krb5_ccache ccache,  
  krb5_flags flags, const char *hostname, krb5_creds *in_creds, krb5_data *out_data);
```

*krb5\_error\_code*

```
krb5_fwd_tgt_creds(krb5_context context, krb5_auth_context auth_context, const char *hostname,  
  krb5_principal client, krb5_principal server, krb5_ccache ccache, int forwardable,  
  krb5_data *out_data);
```

**DESCRIPTION**

**krb5\_get\_forwarded\_creds()** and **krb5\_fwd\_tgt\_creds()** get tickets forwarded to *hostname*. If the tickets that are forwarded are address-less, the forwarded tickets will also be address-less, otherwise *hostname* will be used for figure out the address to forward the ticket too.

**SEE ALSO**

[krb5\(3\)](#), [krb5\\_get\\_credentials\(3\)](#), [krb5.conf\(5\)](#)