

NAME

ldns_rr_list_rr_count, ldns_rr_list_set_rr_count - get and set ldns_rr_list length

SYNOPSIS

```
#include <stdint.h>
```

```
#include <stdbool.h>
```

```
#include <ldns/ldns.h>
```

```
size_t ldns_rr_list_rr_count(const ldns_rr_list *rr_list);
```

```
void ldns_rr_list_set_rr_count(ldns_rr_list *rr_list, size_t count);
```

DESCRIPTION

ldns_rr_list_rr_count() returns the number of rr's in an rr_list.

rr_list: the rr_list to read from

Returns the number of rr's

ldns_rr_list_set_rr_count() sets the number of rr's in an rr_list.

rr_list: the rr_list to set the count on

count: the number of rr in this list

Returns void

AUTHOR

The ldns team at NLnet Labs.

REPORTING BUGS

Please report bugs to ldns-team@nlnetlabs.nl or in our bugzilla at <http://www.nlnetlabs.nl/bugs/index.html>

COPYRIGHT

Copyright (c) 2004 - 2006 NLnet Labs.

Licensed under the BSD License. There is NO warranty; not even for MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.

SEE ALSO

ldns_rr, *ldns_rr_list*. And **perldoc Net::DNS, RFC1034, RFC1035, RFC4033, RFC4034** and **RFC4035**.

REMARKS

This manpage was automatically generated from the ldns source code.