

NAME

`ldns_rr_rdf`, `ldns_rr_owner`, `ldns_rr_rd_count`, `ldns_rr_ttl`, `ldns_rr_get_class` - access rdata fields on `ldns_rr`

SYNOPSIS

```
#include <stdint.h>
#include <stdbool.h>

#include <ldns/ldns.h>

ldns_rdf* ldns_rr_rdf(const ldns_rr *rr, size_t nr);

ldns_rdf* ldns_rr_owner(const ldns_rr *rr);

size_t ldns_rr_rd_count(const ldns_rr *rr);

uint32_t ldns_rr_ttl(const ldns_rr *rr);

ldns_rr_class ldns_rr_get_class(const ldns_rr *rr);
```

DESCRIPTION

`ldns_rr_rdf()` returns the rdata field member counter.

***rr**: rr to operate on

nr: the number of the rdf to return

Returns `ldns_rdf *`

`ldns_rr_owner()` returns the owner name of an rr structure.

***rr**: rr to operate on

Returns `ldns_rdf *`

`ldns_rr_rd_count()` returns the `rd_count` of an rr structure.

***rr**: the rr to read from

Returns the rd count of the rr

`ldns_rr_ttl()` returns the ttl of an rr structure.

***rr**: the rr to read from

Returns the ttl of the rr

`ldns_rr_get_class()` returns the class of the rr.

***rr:** the rr to read from
Returns the class of the rr

AUTHOR

The ldns team at NLnet Labs.

REPORTING BUGS

Please report bugs to ldns-team@nlnetlabs.nl or in our bugzilla at <http://www.nlnetlabs.nl/bugs/index.html>

COPYRIGHT

Copyright (c) 2004 - 2006 NLnet Labs.

Licensed under the BSD License. There is NO warranty; not even for MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.

SEE ALSO

ldns_rr, *ldns_rr_list*. And **perldoc Net::DNS, RFC1034, RFC1035, RFC4033, RFC4034** and **RFC4035**.

REMARKS

This manpage was automatically generated from the ldns source code.