

NAME

ldns_zone_sign, ldns_zone_sign_nsec3 - dnssec sign a zone

SYNOPSIS

```
#include <stdint.h>
```

```
#include <stdbool.h>
```

```
#include <ldns/ldns.h>
```

```
ldns_zone* ldns_zone_sign(const ldns_zone *zone, ldns_key_list *key_list);
```

```
ldns_zone* ldns_zone_sign_nsec3(ldns_zone *zone, ldns_key_list *key_list, uint8_t algorithm, uint8_t flags, uint16_t iterations, uint8_t salt_length, uint8_t *salt);
```

DESCRIPTION

ldns_zone_sign() Signs the zone, and returns a newly allocated signed zone

zone: the zone to sign

key_list: list of keys to sign with

Returns signed zone

ldns_zone_sign_nsec3() Signs the zone with NSEC3, and returns a newly allocated signed zone

zone: the zone to sign

key_list: list of keys to sign with

algorithm: the NSEC3 hashing algorithm to use

flags: NSEC3 flags

iterations: the number of NSEC3 hash iterations to use

salt_length: the length (in octets) of the NSEC3 salt

salt: the NSEC3 salt data

Returns signed zone

AUTHOR

The ldns team at NLnet Labs.

REPORTING BUGS

Please report bugs to ldns-team@nlnetlabs.nl or in our bugzilla at <http://www.nlnetlabs.nl/bugs/index.html>

COPYRIGHT

Copyright (c) 2004 - 2006 NLnet Labs.

Licensed under the BSD License. There is NO warranty; not even for MERCHANTABILITY or FITNESS FOR A PARTICULAR PURPOSE.

SEE ALSO

perldoc Net::DNS, RFC1034, RFC1035, RFC4033, RFC4034 and RFC4035.

REMARKS

This manpage was automatically generated from the ldns source code.