

NAME

syslog, **vsyslog**, **openlog**, **closelog**, **setlogmask** - control system log

LIBRARY

Standard C Library (libc, -lc)

SYNOPSIS

```
#include <syslog.h>
```

void

```
syslog(int priority, const char *message, ...);
```

void

```
openlog(const char *ident, int logopt, int facility);
```

void

```
closelog(void);
```

int

```
setlogmask(int maskpri);
```

```
#include <syslog.h>
```

```
#include <stdarg.h>
```

void

```
vsyslog(int priority, const char *message, va_list args);
```

DESCRIPTION

The **syslog()** function writes *message* to the system message logger. The message is then written to the system console, log files, logged-in users, or forwarded to other machines as appropriate. (See `syslogd(8)`.)

The message is identical to a `printf(3)` format string, except that ‘%m’ is replaced by the current error message. (As denoted by the global variable *errno*; see `strerror(3)`.) A trailing newline is added if none is present.

The **vsyslog()** function is an alternate form in which the arguments have already been captured using the variable-length argument facilities of `stdarg(3)`.

The message is tagged with *priority*. Priorities are encoded as a *facility* and a *level*. The facility

describes the part of the system generating the message. The level is selected from the following *ordered* (high to low) list:

| | |
|-------------|--|
| LOG_EMERG | A panic condition. This is normally broadcast to all users. |
| LOG_ALERT | A condition that should be corrected immediately, such as a corrupted system database. |
| LOG_CRIT | Critical conditions, e.g., hard device errors. |
| LOG_ERR | Errors. |
| LOG_WARNING | Warning messages. |
| LOG_NOTICE | Conditions that are not error conditions, but should possibly be handled specially. |
| LOG_INFO | Informational messages. |
| LOG_DEBUG | Messages that contain information normally of use only when debugging a program. |

The **openlog()** function provides for more specialized processing of the messages sent by **syslog()** and **vsyslog()**. The *ident* argument is a string that will be prepended to every message. It may be formatted as *ident[N]* in which case decimal number *N* replaces the process id within messages. The *logopt* argument is a bit field specifying logging options, which is formed by OR'ing one or more of the following values:

| | |
|------------|---|
| LOG_CONS | If syslog() cannot pass the message to syslogd(8) it will attempt to write the message to the console (" <i>/dev/console</i> "). |
| LOG_NDELAY | Open the connection to syslogd(8) immediately. Normally the open is delayed until the first message is logged. Useful for programs that need to manage the order in which file descriptors are allocated. |
| LOG_PERROR | Write the message to standard error output as well to the system log. |
| LOG_PID | Log the process id with each message: useful for identifying instantiations of daemons. On FreeBSD, this option is enabled by default and cannot be disabled. |

The *facility* argument encodes a default facility to be assigned to all messages that do not have an explicit facility encoded:

| | |
|--------------|--|
| LOG_AUTH | The authorization system: login(1), su(1), getty(8), etc. |
| LOG_AUTHPRIV | The same as LOG_AUTH, but logged to a file readable only by selected individuals. |
| LOG_CONSOLE | Messages written to <i>/dev/console</i> by the kernel console output driver. |
| LOG_CRON | The cron daemon: cron(8). |
| LOG_DAEMON | System daemons, such as routed(8), that are not provided for explicitly by other facilities. |
| LOG_FTP | The file transfer protocol daemons: ftpd(8), tftpd(8). |
| LOG_KERN | Messages generated by the kernel. These cannot be generated by any user processes. |
| LOG_LPR | The line printer spooling system: lpr(1), lpc(8), lpd(8), etc. |
| LOG_MAIL | The mail system. |
| LOG_NEWS | The network news system. |
| LOG_NTP | The network time protocol system. |
| LOG_SECURITY | Security subsystems, such as ipfw(4). |
| LOG_SYSLOG | Messages generated internally by syslogd(8). |
| LOG_USER | Messages generated by random user processes. This is the default facility identifier if none is specified. |
| LOG_UUCP | The uucp system. |
| LOG_LOCAL0 | Reserved for local use. Similarly for LOG_LOCAL1 through LOG_LOCAL7. |

The **closelog()** function can be used to close the log file.

The **setlogmask()** function sets the log priority mask to *maskpri* and returns the previous mask. Calls to **syslog()** with a priority not set in *maskpri* are rejected. The mask for an individual priority *pri* is calculated by the macro **LOG_MASK(pri)**; the mask for all priorities up to and including *toppri* is given

by the macro **LOG_UPTO**(*toppri*);. The default allows all priorities to be logged.

RETURN VALUES

The routines **closelog**(), **openlog**(), **syslog**() and **vsyslog**() return no value.

The routine **setlogmask**() always returns the previous log mask level.

EXAMPLES

```
syslog(LOG_ALERT, "who: internal error 23");

openlog("ftpd", LOG_PID | LOG_NDELAY, LOG_FTP);

setlogmask(LOG_UPTO(LOG_ERR));

syslog(LOG_INFO, "Connection from host %d", CallingHost);

syslog(LOG_ERR|LOG_LOCAL2, "foobar error: %m");
```

SEE ALSO

logger(1), syslogd(8)

HISTORY

These functions appeared in 4.2BSD.

BUGS

Never pass a string with user-supplied data as a format without using '%s'. An attacker can put format specifiers in the string to mangle your stack, leading to a possible security hole. This holds true even if the string was built using a function like **snprintf**(), as the resulting string may still contain user-supplied conversion specifiers for later interpolation by **syslog**().

Always use the proper secure idiom:

```
syslog(priority, "%s", string);
```