

NAME

pam_putenv - set the value of an environment variable

SYNOPSIS

```
#include <sys/types.h>
#include <security/pam_appl.h>
```

int

```
pam_putenv(pam_handle_t *pamh, const char *namevalue);
```

DESCRIPTION

The **pam_putenv()** function sets an environment variable. Its semantics are similar to those of **putenv(3)**, but it modifies the PAM context's environment list instead of the application's.

RETURN VALUES

The **pam_putenv()** function returns one of the following values:

[PAM_SUCCESS] Success.

[PAM_BUF_ERR] Memory buffer error.

[PAM_SYSTEM_ERR] System error.

SEE ALSO

pam(3), **pam_getenv(3)**, **pam_getenvlist(3)**, **pam_setenv(3)**, **pam_strerror(3)**, **putenv(3)**

STANDARDS

X/Open Single Sign-On Service (XSSO) - Pluggable Authentication Modules, June 1997.

AUTHORS

The **pam_putenv()** function and this manual page were developed for the FreeBSD Project by ThinkSec AS and Network Associates Laboratories, the Security Research Division of Network Associates, Inc. under DARPA/SPAWAR contract N66001-01-C-8035 ("CBOSS"), as part of the DARPA CHATS research program.

The OpenPAM library is maintained by Dag-Erling Smørgrav <*des@des.no*>.