

NAME

posix_spawn_file_actions_init, **posix_spawn_file_actions_destroy** - initialize and destroy spawn file actions object

LIBRARY

Standard C Library (libc, -lc)

SYNOPSIS

```
#include <spawn.h>
```

int

```
posix_spawn_file_actions_init(posix_spawn_file_actions_t *file_actions);
```

int

```
posix_spawn_file_actions_destroy(posix_spawn_file_actions_t *file_actions);
```

DESCRIPTION

The **posix_spawn_file_actions_init**() function initialize the object referenced by **file_actions**() to contain no file actions for **posix_spawn**() or **posix_spawnnp**(). Initializing an already initialized spawn file actions object may cause memory to be leaked.

The **posix_spawn_file_actions_destroy**() function destroy the object referenced by *file_actions*; the object becomes, in effect, uninitialized. A destroyed spawn file actions object can be reinitialized using **posix_spawn_file_actions_init**(). The object should not be used after it has been destroyed.

RETURN VALUES

Upon successful completion, these functions return zero; otherwise, an error number is returned to indicate the error.

ERRORS

The **posix_spawn_file_actions_init**() function will fail if:

[ENOMEM]	Insufficient memory exists to initialize the spawn file actions object.
----------	---

SEE ALSO

posix_spawn(3), posix_spawn_file_actions_addclose(3),
posix_spawn_file_actions_addclosefrom_np(3), posix_spawn_file_actions_adddup2(3),
posix_spawn_file_actions_addopen(3), posix_spawnnp(3)

STANDARDS

The **posix_spawn_file_actions_init()** and **posix_spawn_file_actions_destroy()** functions conform to IEEE Std 1003.1-2001 ("POSIX.1").

HISTORY

The **posix_spawn_file_actions_init()** and **posix_spawn_file_actions_destroy()** functions first appeared in FreeBSD 8.0.

AUTHORS

Ed Schouten <*ed@FreeBSD.org*>