

**NAME**

**sdiff** - side-by-side diff

**SYNOPSIS**

**sdiff** [-**abdilstHW**] [-**I** *regex*] [-**o** *outfile*] [-**w** *width*] *file1 file2*

**DESCRIPTION**

**sdiff** displays two files side by side, with any differences between the two highlighted as follows: new lines are marked with '>'; deleted lines are marked with '<'; and changed lines are marked with '|'.

**sdiff** can also be used to interactively merge two files, prompting at each set of differences. See the **-o** option for an explanation.

The options are:

**-l --left-column**

Only print the left column for identical lines.

**-o --output** *outfile*

Interactively merge *file1* and *file2* into *outfile*. In this mode, the user is prompted for each set of differences. See EDITOR and VISUAL, below, for details of which editor, if any, is invoked.

The commands are as follows:

**l | 1** Choose left set of diffs.

**r | 2** Choose right set of diffs.

**s** Silent mode - identical lines are not printed.

**v** Verbose mode - identical lines are printed.

**e** Start editing an empty file, which will be merged into *outfile* upon exiting the editor.

**e l** Start editing file with left set of diffs.

**e r** Start editing file with right set of diffs.

**e b** Start editing file with both sets of diffs.

**q** Quit **sdiff**.

**-s --suppress-common-lines**

Skip identical lines.

**-w --width** *width*

Print a maximum of *width* characters on each line. The default is 130 characters.

Options passed to `diff(1)` are:

**-a --text**

Treat *file1* and *file2* as text files.

**-b --ignore-space-change**

Ignore trailing blank spaces.

**-d --minimal**

Minimize diff size.

**-I --ignore-matching-lines** *regex*

Ignore line changes matching *regex*. All lines in the change must match *regex* for the change to be ignored.

**-i --ignore-case**

Do a case-insensitive comparison.

**-t --expand-tabs**

Expand tabs to spaces.

**-W --ignore-all-space**

Ignore all spaces.

**-B --ignore-blank-lines**

Ignore blank lines.

**-E --ignore-tab-expansion**

Treat tabs and eight spaces as the same.

**-t --ignore-tabs**

Ignore tabs.

**-H --speed-large-files**

Assume scattered small changes in a large file.

**--ignore-file-name-case**

Ignore the case of file names.

**--no-ignore-file-name-case**

Do not ignore file name case.

**--strip-trailing-cr**

Skip identical lines.

**--tabsize *NUM***

Change the size of tabs (default is 8.)

**ENVIRONMENT****EDITOR, VISUAL**

Specifies an editor to use with the **-o** option. If both **EDITOR** and **VISUAL** are set, **VISUAL** takes precedence. If neither **EDITOR** nor **VISUAL** are set, the default is **vi(1)**.

**TMPDIR**

Specifies a directory for temporary files to be created. The default is */tmp*.

**SEE ALSO**

**cmp(1)**, **diff(1)**, **diff3(1)**, **vi(1)**, **re\_format(7)**

**AUTHORS**

**sdiff** was written from scratch for the public domain by Ray Lai <ray@cyth.net>.

**CAVEATS**

Tabs are treated as anywhere from one to eight characters wide, depending on the current column. Terminals that treat tabs as eight characters wide will look best.