NAME

sighold, sigignore, sigpause, sigrelse, sigset - legacy interface for signal management

LIBRARY

```
Standard C Library (libc, -lc)
```

SYNOPSIS

```
#include <signal.h>

int
sighold(int sig);

int
sigignore(int sig);

int
xsi_sigpause(int sigmask);

int
sigrelse(int sig);

void (*)(int)
sigset(int, void (*disp)(int));

int
sigpause(int sigmask);
```

DESCRIPTION

This interface is made obsolete by sigsuspend(2) and sigaction(2).

The **sigset**() function modifies signal dispositions. The *sig* argument specifies the signal, which may be any signal except SIGKILL and SIGSTOP. The *disp* argument specifies the signal's disposition, which may be SIG_DFL, SIG_IGN, or the address of a signal handler. If **sigset**() is used, and *disp* is the address of a signal handler, the system adds *sig* to the signal mask of the calling process before executing the signal handler; when the signal handler returns, the system restores the signal mask of the calling process to its state prior to the delivery of the signal. In addition, if **sigset**() is used, and *disp* is equal to SIG_HOLD, *sig* is added to the signal mask of the calling process and *sig* 's disposition remains unchanged. If **sigset**() is used, and *disp* is not equal to SIG_HOLD, *sig* is removed from the signal mask of the calling process.

The **sighold**() function adds *sig* to the signal mask of the calling process.

The **sigrelse**() function removes *sig* from the signal mask of the calling process.

The **sigignore**() function sets the disposition of *sig* to SIG_IGN.

The **xsi_sigpause**() function removes *sig* from the signal mask of the calling process and suspend the calling process until a signal is received. The **xsi_sigpause**() function restores the signal mask of the process to its original state before returning.

The **sigpause**() function assigns *sigmask* to the set of masked signals and then waits for a signal to arrive; on return the set of masked signals is restored. The *sigmask* argument is usually 0 to indicate that no signals are to be blocked.

RETURN VALUES

The **sigpause**() and **xsi_sigpause**() functions always terminate by being interrupted, returning -1 with *errno* set to EINTR.

Upon successful completion, **sigset**() returns SIG_HOLD if the signal had been blocked and the signal's previous disposition if it had not been blocked. Otherwise, SIG_ERR is returned and *errno* set to indicate the error.

For all other functions, upon successful completion, 0 is returned. Otherwise, -1 is returned and *errno* is set to indicate the error:

[EINVAL] The *sig* argument is not a valid signal number.

[EINVAL] For **sigset**() and **sigignore**() functions, an attempt was made to catch or ignore SIGKILL or SIGSTOP.

SEE ALSO

kill(2), sigaction(2), sigblock(2), sigprocmask(2), sigsuspend(2), sigvec(2)

STANDARDS

The **sigpause**() function is implemented for compatibility with historic 4.3BSD applications. An incompatible interface by the same name, which used a single signal number rather than a mask, was present in AT&T System V UNIX, and was copied from there into the **X/Open System Interfaces** (XSI) option of IEEE Std 1003.1-2001 ("POSIX.1"). FreeBSD implements it under the name **xsi_sigpause**(). The **sighold**(), **sigignore**(), **sigrelse**() and **sigset**() functions are implemented for compatibility with **System V** and **XSI** interfaces.

HISTORY

The **sigpause**() function appeared in 4.2BSD and has been deprecated. All other functions appeared in FreeBSD 8.1 and were deprecated before being implemented.