

NAME

stringprep_ucs4_to_utf8 - API function

SYNOPSIS

```
#include <stringprep.h>
```

```
char * stringprep_ucs4_to_utf8(const uint32_t * str, ssize_t len, size_t * items_read, size_t * items_written);
```

ARGUMENTS

const uint32_t * str

a UCS-4 encoded string

ssize_t len the maximum length of *str* to use. If *len* < 0, then the string is terminated with a 0 character.

size_t * items_read

location to store number of characters read read, or **NULL**.

size_t * items_written

location to store number of bytes written or **NULL**. The value here stored does not include the trailing 0 byte.

DESCRIPTION

Convert a string from a 32-bit fixed width representation as UCS-4. to UTF-8. The result will be terminated with a 0 byte.

Return value: a pointer to a newly allocated UTF-8 string. This value must be deallocated by the caller. If an error occurs, **NULL** will be returned.

REPORTING BUGS

Report bugs to <help-libidn@gnu.org>.

General guidelines for reporting bugs: <http://www.gnu.org/gethelp/>

GNU Libidn home page: <http://www.gnu.org/software/libidn/>

COPYRIGHT

Copyright (C) 2002-2021 Simon Josefsson.

Copying and distribution of this file, with or without modification, are permitted in any medium without royalty provided the copyright notice and this notice are preserved.

SEE ALSO

The full documentation for **libidn** is maintained as a Texinfo manual. If the **info** and **libidn** programs are properly installed at your site, the command

info libidn

should give you access to the complete manual. As an alternative you may obtain the manual from:

<http://www.gnu.org/software/libidn/manual/>