

**NAME**

`xcb_input_raw_key_press_event_t` -

**SYNOPSIS**

```
#include <xcb/xinput.h>
```

**Event datastructure**

```
typedef struct xcb_input_raw_key_press_event_t {
    uint8_t      response_type;
    uint8_t      extension;
    uint16_t     sequence;
    uint32_t     length;
    uint16_t     event_type;
    xcb_input_device_id_t deviceid;
    xcb_timestamp_t time;
    uint32_t     detail;
    xcb_input_device_id_t sourceid;
    uint16_t     valuators_len;
    uint32_t     flags;
    uint8_t      pad0[4];
    uint32_t     full_sequence;
} xcb_input_raw_key_press_event_t;
```

**EVENT FIELDS**

*response\_type* The type of this event, in this case *XCB\_INPUT\_RAW\_KEY\_RELEASE*. This field is also present in the *xcb\_generic\_event\_t* and can be used to tell events apart from each other.

*sequence* The sequence number of the last request processed by the X11 server.

*extension* NOT YET DOCUMENTED.

*length* NOT YET DOCUMENTED.

*event\_type* NOT YET DOCUMENTED.

*deviceid* NOT YET DOCUMENTED.

*time* NOT YET DOCUMENTED.

*detail* NOT YET DOCUMENTED.

*sourceid* NOT YET DOCUMENTED.

*valuators\_len* NOT YET DOCUMENTED.

*flags* NOT YET DOCUMENTED.

*full\_sequence* NOT YET DOCUMENTED.

## DESCRIPTION

## SEE ALSO

## AUTHOR

Generated from xinput.xml. Contact xcb@lists.freedesktop.org for corrections and improvements.