

NAME

xcb_input_xi_passive_ungrab_device -

SYNOPSIS

```
#include <xcb/xinput.h>
```

Request function

```
xcb_void_cookie_t xcb_input_xi_passive_ungrab_device(xcb_connection_t *conn,  
    xcb_window_t grab_window, uint32_t detail, xcb_input_device_id_t deviceid,  
    uint16_t num_modifiers, uint8_t grab_type, const uint32_t *modifiers);
```

REQUEST ARGUMENTS

conn The XCB connection to X11.

grab_window TODO: NOT YET DOCUMENTED.

detail TODO: NOT YET DOCUMENTED.

deviceid TODO: NOT YET DOCUMENTED.

num_modifiers TODO: NOT YET DOCUMENTED.

grab_type TODO: NOT YET DOCUMENTED.

modifiers TODO: NOT YET DOCUMENTED.

DESCRIPTION

RETURN VALUE

Returns an *xcb_void_cookie_t*. Errors (if any) have to be handled in the event loop.

If you want to handle errors directly with *xcb_request_check* instead, use *xcb_input_xi_passive_ungrab_device_checked*. See **xcb-requests(3)** for details.

ERRORS

This request does never generate any errors.

SEE ALSO

AUTHOR

Generated from xinput.xml. Contact xcb@lists.freedesktop.org for corrections and improvements.