

NAME

`xcb_randr_get_output_primary` -

SYNOPSIS

```
#include <xcb/randr.h>
```

Request function

```
xcb_randr_get_output_primary_cookie_t xcb_randr_get_output_primary(xcb_connection_t *conn,  
xcb_window_t window);
```

Reply datastructure

```
typedef struct xcb_randr_get_output_primary_reply_t {  
    uint8_t      response_type;  
    uint8_t      pad0;  
    uint16_t     sequence;  
    uint32_t     length;  
    xcb_randr_output_t output;  
} xcb_randr_get_output_primary_reply_t;
```

Reply function

```
xcb_randr_get_output_primary_reply_t  
*xcb_randr_get_output_primary_reply(xcb_connection_t *conn,  
xcb_randr_get_output_primary_cookie_t cookie, xcb_generic_error_t **e);
```

REQUEST ARGUMENTS

conn The XCB connection to X11.

window TODO: NOT YET DOCUMENTED.

REPLY FIELDS

response_type The type of this reply, in this case *XCB_RANDR_GET_OUTPUT_PRIMARY*. This field is also present in the *xcb_generic_reply_t* and can be used to tell replies apart from each other.

sequence The sequence number of the last request processed by the X11 server.

length The length of the reply, in words (a word is 4 bytes).

output TODO: NOT YET DOCUMENTED.

DESCRIPTION**RETURN VALUE**

Returns an *xcb_randr_get_output_primary_cookie_t*. Errors have to be handled when calling the reply function *xcb_randr_get_output_primary_reply*.

If you want to handle errors in the event loop instead, use *xcb_randr_get_output_primary_unchecked*.

See **xcb-requests(3)** for details.

ERRORS

This request does never generate any errors.

SEE ALSO**AUTHOR**

Generated from randr.xml. Contact xcb@lists.freedesktop.org for corrections and improvements.