

**NAME**

xcb\_randr\_set\_crtc\_transform -

**SYNOPSIS**

```
#include <xcb/randr.h>
```

**Request function**

```
xcb_void_cookie_t xcb_randr_set_crtc_transform(xcb_connection_t *conn, xcb_randr_crtc_t crtc,  
        xcb_render_transform_t transform, uint16_t filter_len, const char *filter_name,  
        uint32_t filter_params_len, const xcb_render_fixed_t *filter_params);
```

**REQUEST ARGUMENTS**

*conn*            The XCB connection to X11.

*crtc*            TODO: NOT YET DOCUMENTED.

*transform*        TODO: NOT YET DOCUMENTED.

*filter\_len*        TODO: NOT YET DOCUMENTED.

*filter\_name*      TODO: NOT YET DOCUMENTED.

*filter\_params\_len*  
                  TODO: NOT YET DOCUMENTED.

*filter\_params*    TODO: NOT YET DOCUMENTED.

**DESCRIPTION****RETURN VALUE**

Returns an *xcb\_void\_cookie\_t*. Errors (if any) have to be handled in the event loop.

If you want to handle errors directly with *xcb\_request\_check* instead, use *xcb\_randr\_set\_crtc\_transform\_checked*. See **xcb-requests(3)** for details.

**ERRORS**

This request does never generate any errors.

**SEE ALSO****AUTHOR**

Generated from randr.xml. Contact [xcb@lists.freedesktop.org](mailto:xcb@lists.freedesktop.org) for corrections and improvements.