

NAME

xcb_render_add_glyphs -

SYNOPSIS

```
#include <xcb/render.h>
```

Request function

```
xcb_void_cookie_t xcb_render_add_glyphs(xcb_connection_t *conn, xcb_render_glyphset_t glyphset,  
uint32_t glyphs_len, const uint32_t *glyphids, const xcb_render_glyphinfo_t *glyphs,  
uint32_t data_len, const uint8_t *data);
```

REQUEST ARGUMENTS

<i>conn</i>	The XCB connection to X11.
<i>glyphset</i>	TODO: NOT YET DOCUMENTED.
<i>glyphs_len</i>	TODO: NOT YET DOCUMENTED.
<i>glyphids</i>	TODO: NOT YET DOCUMENTED.
<i>glyphs</i>	TODO: NOT YET DOCUMENTED.
<i>data_len</i>	TODO: NOT YET DOCUMENTED.
<i>data</i>	TODO: NOT YET DOCUMENTED.

DESCRIPTION**RETURN VALUE**

Returns an *xcb_void_cookie_t*. Errors (if any) have to be handled in the event loop.

If you want to handle errors directly with *xcb_request_check* instead, use *xcb_render_add_glyphs_checked*. See **xcb-requests(3)** for details.

ERRORS

This request does never generate any errors.

SEE ALSO**AUTHOR**

Generated from render.xml. Contact xcb@lists.freedesktop.org for corrections and improvements.