

NAME

xcb_render_create_linear_gradient -

SYNOPSIS

```
#include <xcb/render.h>
```

Request function

```
xcb_void_cookie_t xcb_render_create_linear_gradient(xcb_connection_t *conn,  
    xcb_render_picture_t picture, xcb_render_pointfix_t p1, xcb_render_pointfix_t p2,  
    uint32_t num_stops, const xcb_render_fixed_t *stops, const xcb_render_color_t *colors);
```

REQUEST ARGUMENTS

<i>conn</i>	The XCB connection to X11.
<i>picture</i>	TODO: NOT YET DOCUMENTED.
<i>p1</i>	TODO: NOT YET DOCUMENTED.
<i>p2</i>	TODO: NOT YET DOCUMENTED.
<i>num_stops</i>	TODO: NOT YET DOCUMENTED.
<i>stops</i>	TODO: NOT YET DOCUMENTED.
<i>colors</i>	TODO: NOT YET DOCUMENTED.

DESCRIPTION**RETURN VALUE**

Returns an *xcb_void_cookie_t*. Errors (if any) have to be handled in the event loop.

If you want to handle errors directly with *xcb_request_check* instead, use *xcb_render_create_linear_gradient_checked*. See **xcb-requests(3)** for details.

ERRORS

This request does never generate any errors.

SEE ALSO**AUTHOR**

Generated from render.xml. Contact xcb@lists.freedesktop.org for corrections and improvements.