

**NAME**

xcb\_render\_tri\_fan -

**SYNOPSIS**

```
#include <xcb/render.h>
```

**Request function**

```
xcb_void_cookie_t xcb_render_tri_fan(xcb_connection_t *conn, uint8_t op, xcb_render_picture_t src,  
    xcb_render_picture_t dst, xcb_render_pictformat_t mask_format, int16_t src_x, int16_t src_y,  
    uint32_t points_len, const xcb_render_pointfix_t *points);
```

**REQUEST ARGUMENTS**

|                    |                            |
|--------------------|----------------------------|
| <i>conn</i>        | The XCB connection to X11. |
| <i>op</i>          | TODO: NOT YET DOCUMENTED.  |
| <i>src</i>         | TODO: NOT YET DOCUMENTED.  |
| <i>dst</i>         | TODO: NOT YET DOCUMENTED.  |
| <i>mask_format</i> | TODO: NOT YET DOCUMENTED.  |
| <i>src_x</i>       | TODO: NOT YET DOCUMENTED.  |
| <i>src_y</i>       | TODO: NOT YET DOCUMENTED.  |
| <i>points_len</i>  | TODO: NOT YET DOCUMENTED.  |
| <i>points</i>      | TODO: NOT YET DOCUMENTED.  |

**DESCRIPTION****RETURN VALUE**

Returns an *xcb\_void\_cookie\_t*. Errors (if any) have to be handled in the event loop.

If you want to handle errors directly with *xcb\_request\_check* instead, use *xcb\_render\_tri\_fan\_checked*. See **xcb-requests(3)** for details.

**ERRORS**

This request does never generate any errors.

**SEE ALSO**

**AUTHOR**

Generated from render.xml. Contact [xcb@lists.freedesktop.org](mailto:xcb@lists.freedesktop.org) for corrections and improvements.