

**NAME**

xcb\_set\_close\_down\_mode -

**SYNOPSIS**

```
#include <xcb/xproto.h>
```

**Request function**

```
xcb_void_cookie_t xcb_set_close_down_mode(xcb_connection_t *conn, uint8_t mode);
```

**REQUEST ARGUMENTS**

*conn*            The XCB connection to X11.

*mode*            One of the following values:

```
XCB_CLOSE_DOWN_DESTROY_ALL  
                  TODO: NOT YET DOCUMENTED.
```

```
XCB_CLOSE_DOWN_RETAIN_PERMANENT  
                  TODO: NOT YET DOCUMENTED.
```

```
XCB_CLOSE_DOWN_RETAIN_TEMPORARY  
                  TODO: NOT YET DOCUMENTED.  
                  TODO: NOT YET DOCUMENTED.
```

**DESCRIPTION****RETURN VALUE**

Returns an *xcb\_void\_cookie\_t*. Errors (if any) have to be handled in the event loop.

If you want to handle errors directly with *xcb\_request\_check* instead, use *xcb\_set\_close\_down\_mode\_checked*. See **xcb-requests(3)** for details.

**ERRORS**

This request does never generate any errors.

**SEE ALSO****AUTHOR**

Generated from xproto.xml. Contact [xcb@lists.freedesktop.org](mailto:xcb@lists.freedesktop.org) for corrections and improvements.