

**NAME**

xcb\_ungrab\_button -

**SYNOPSIS**

```
#include <xcb/xproto.h>
```

**Request function**

```
xcb_void_cookie_t xcb_ungrab_button(xcb_connection_t *conn, uint8_t button,  
xcb_window_t grab_window, uint16_t modifiers);
```

**REQUEST ARGUMENTS**

*conn*           The XCB connection to X11.

*button*           One of the following values:

*XCB\_BUTTON\_INDEX\_ANY*

Any of the following (or none):

*XCB\_BUTTON\_INDEX\_1*

The left mouse button.

*XCB\_BUTTON\_INDEX\_2*

The right mouse button.

*XCB\_BUTTON\_INDEX\_3*

The middle mouse button.

*XCB\_BUTTON\_INDEX\_4*

Scroll wheel. TODO: direction?

*XCB\_BUTTON\_INDEX\_5*

Scroll wheel. TODO: direction?

TODO: NOT YET DOCUMENTED.

*grab\_window*    TODO: NOT YET DOCUMENTED.

*modifiers*        TODO: NOT YET DOCUMENTED.

**DESCRIPTION****RETURN VALUE**

Returns an *xcb\_void\_cookie\_t*. Errors (if any) have to be handled in the event loop.

If you want to handle errors directly with *xcb\_request\_check* instead, use *xcb\_ungrab\_button\_checked*. See **xcb-requests(3)** for details.

## **ERRORS**

This request does never generate any errors.

## **SEE ALSO**

## **AUTHOR**

Generated from xproto.xml. Contact [xcb@lists.freedesktop.org](mailto:xcb@lists.freedesktop.org) for corrections and improvements.