

NAME

xcb_xfixes_create_pointer_barrier -

SYNOPSIS

```
#include <xcb/xfixes.h>
```

Request function

```
xcb_void_cookie_t xcb_xfixes_create_pointer_barrier(xcb_connection_t *conn,  
    xcb_xfixes_barrier_t barrier, xcb_window_t window, uint16_t x1, uint16_t y1, uint16_t x2,  
    uint16_t y2, uint32_t directions, uint16_t num_devices, const uint16_t *devices);
```

REQUEST ARGUMENTS

<i>conn</i>	The XCB connection to X11.
<i>barrier</i>	TODO: NOT YET DOCUMENTED.
<i>window</i>	TODO: NOT YET DOCUMENTED.
<i>x1</i>	TODO: NOT YET DOCUMENTED.
<i>y1</i>	TODO: NOT YET DOCUMENTED.
<i>x2</i>	TODO: NOT YET DOCUMENTED.
<i>y2</i>	TODO: NOT YET DOCUMENTED.
<i>directions</i>	TODO: NOT YET DOCUMENTED.
<i>num_devices</i>	TODO: NOT YET DOCUMENTED.
<i>devices</i>	TODO: NOT YET DOCUMENTED.

DESCRIPTION**RETURN VALUE**

Returns an *xcb_void_cookie_t*. Errors (if any) have to be handled in the event loop.

If you want to handle errors directly with *xcb_request_check* instead, use *xcb_xfixes_create_pointer_barrier_checked*. See **xcb-requests(3)** for details.

ERRORS

This request does never generate any errors.

SEE ALSO

AUTHOR

Generated from xfixes.xml. Contact xcb@lists.freedesktop.org for corrections and improvements.