

NAME

xcb_xfixes_expand_region -

SYNOPSIS

```
#include <xcb/xfixes.h>
```

Request function

```
xcb_void_cookie_t xcb_xfixes_expand_region(xcb_connection_t *conn, xcb_xfixes_region_t source,  
xcb_xfixes_region_t destination, uint16_t left, uint16_t right, uint16_t top, uint16_t bottom);
```

REQUEST ARGUMENTS

<i>conn</i>	The XCB connection to X11.
<i>source</i>	TODO: NOT YET DOCUMENTED.
<i>destination</i>	TODO: NOT YET DOCUMENTED.
<i>left</i>	TODO: NOT YET DOCUMENTED.
<i>right</i>	TODO: NOT YET DOCUMENTED.
<i>top</i>	TODO: NOT YET DOCUMENTED.
<i>bottom</i>	TODO: NOT YET DOCUMENTED.

DESCRIPTION**RETURN VALUE**

Returns an *xcb_void_cookie_t*. Errors (if any) have to be handled in the event loop.

If you want to handle errors directly with *xcb_request_check* instead, use *xcb_xfixes_expand_region_checked*. See **xcb-requests(3)** for details.

ERRORS

This request does never generate any errors.

SEE ALSO**AUTHOR**

Generated from xfixes.xml. Contact xcb@lists.freedesktop.org for corrections and improvements.