NAME
     xcb_xkb_get_indicator_map -

SYNOPSIS
     #include <xcb/xkb.h>

  Request function
     xcb_xkb_get_indicator_map_cookie_t **xcb_xkb_get_indicator_map**(xcb_connection_t *_conn_,
         xcb_xkb_device_spec_t _deviceSpec_, uint32_t _which_);

  Reply datastructure

     typedef struct xcb_xkb_get_indicator_map_reply_t {
        uint8_t _response_type_;
        uint8_t _deviceID_;
        uint16_t _sequence_;
        uint32_t _length_;
        uint32_t _which_;
        uint32_t _realIndicators_;
        uint8_t _nIndicators_;
        uint8_t _pad0_[15];
     } **xcb_xkb_get_indicator_map_reply_t**;

  Reply function
     xcb_xkb_get_indicator_map_reply_t ***xcb_xkb_get_indicator_map_reply**(xcb_connection_t *_conn_,
         xcb_xkb_get_indicator_map_cookie_t _cookie_, xcb_generic_error_t **_e_);

  Reply accessors
     xcb_xkb_indicator_map_t ***xcb_xkb_get_indicator_map_maps**(const
         xcb_xkb_get_indicator_map_request_t *_reply_);

     int **xcb_xkb_get_indicator_map_maps_length**(const xcb_xkb_get_indicator_map_reply_t *_reply_);

     xcb_xkb_indicator_map_iterator_t **xcb_xkb_get_indicator_map_maps_iterator**(const
         xcb_xkb_get_indicator_map_reply_t *_reply_);

REQUEST ARGUMENTS
     conn   The XCB connection to X11.

     deviceSpec   TODO: NOT YET DOCUMENTED.

which   TODO: NOT YET DOCUMENTED.

REPLY FIELDS

response_type   The type of this reply, in this case *XCB_XKB_GET_INDICATOR_MAP*. This field is also present in the *xcb_generic_reply_t* and can be used to tell replies apart from each other.

sequence   The sequence number of the last request processed by the X11 server.

length   The length of the reply, in words (a word is 4 bytes).

deviceID   TODO: NOT YET DOCUMENTED.

which   TODO: NOT YET DOCUMENTED.

realIndicators   TODO: NOT YET DOCUMENTED.

nIndicators   TODO: NOT YET DOCUMENTED.

DESCRIPTION
RETURN VALUE

Returns an *xcb_xkb_get_indicator_map_cookie_t*. Errors have to be handled when calling the reply function *xcb_xkb_get_indicator_map_reply*.

If you want to handle errors in the event loop instead, use *xcb_xkb_get_indicator_map_unchecked*. See **xcb-requests(3)** for details.

ERRORS

This request does never generate any errors.

SEE ALSO
AUTHOR

Generated from xkb.xml. Contact xcb@lists.freedesktop.org for corrections and improvements.